

# NC-MCS06-560-RKIT

## Intelligent conventional Swedish manual call point kit, surface mount with flip cover

### Product overview

---

The NC-MCS06-560-RKIT is a red manual call point with back box and flip cover for surface mount applications.

The call point offers one normally open contact in series with a 560  $\Omega$  resistor, as well as a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a EN54 style resettable element, pluggable connectors for both contacts, a handy wire bridge to help with cable continuity testing, as well as a test key that doubles up as a service tool for disassembly of the device. A colour matched back box and protection flip cover is included, together with a protection seal to lock the flip cover to the manual call point.

### Installation

---

Installation time and installation flexibility are of paramount importance. The Carrier MCP range directly meets these needs by providing features designed specifically for this. Pluggable terminal blocks facilitate the pre-connection of all cables. This terminal block is then simply connected to the MCP. Should continuity testing be needed, the handy wire bridge fits neatly into the terminal block in place of the MCP without having to disconnect any cables.

For service and maintenance no additional tools other than the test key is needed. With easy front access in all installations and even with the protection cover fitted, the test key is also used to remove the front cover of the unit should a frangible element need to be replaced.

### Options

---

Both break glass (frangible elements) and re-settable operating elements may be used. The MCP can be configured as either a break glass or re-settable unit by simply changing from one element to another. Other than the optional frangible element, no additional parts are required. Other parts and accessories include metal test keys and replacement parts.

This range of manual call points is available in various colours with various trigger resistor options to suit most applications. In addition various function markings are available including regional language variants.



### Details

---

- Specifically designed for manual fire alarm activation
- Alarm indication by alarm flag and alarm LED
- Enhanced aesthetics with screen printed, high resolution functional marking
- Resettable and also usable with an optional frangible element
- Easy to install (plug and play)
- Colour matched surface mount back box included
- With protection hinged cover with anti-tamper facilities for accidental activation prevention
- Key test facility from the front of the unit for easy access, even when a protection cover is fitted
- Easy service and maintenance with test key disassembly and pluggable connectors

# NC-MCS06-560-RKIT

Intelligent conventional Swedish manual call point kit, surface mount with flip cover

## Technical specifications

### General

Status indication	LED & alarm flag
Compatibility	Conventional alarm systems
Connectivity	2-wire zone

### Electrical

Power supply type	Zone powered
Operating voltage	20 to 24 VDC
Current consumption	0 mA (standby) 25 mA (alarm)
Cable specification	0.404 to 2.05 mm (0.13 to 3.31 mm <sup>2</sup> )
No. of cable cores	2
Terminals	7

### Detection

Detection principle	Manual activation
Monitoring	Activated, Off
Täckningsområde	Region specific
Zone length	<2 km, CIE specific
Response time	< 3 s
Installation height	Determined by local regulation

### Output

Output quantity	2
Output type and rating	1 x NO resistor limited, 1 x change over relay 1 A @ 24 VDC

### Physical


Physical dimensions	87 x 87 x 26 mm (W x H x D) - MCP 87 x 87 x 35 mm (W x H x D) - Back box 94 x 109 x 24 mm (W x H x D) - Flip cover
Net weight	101 g - MCP 60 g - Back box 60 g - Flip cover
Colour	Red (RAL 3028)
Mounting type	Back box, Wall mount
Cable entries	4
Material (body)	Flame retardent ABS
Functional marking	House on fire, BRAND-LARM

### Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-25 to +70°C
Relative humidity	10 to 95% noncondensing
Miljö	Indoor
IP rating	IP41

### Regulatory

Compliance	CE, REACH, RoHS 3, WEEE
Intygande	CPR
Standards	EN54-11



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök [se.firesecurityproducts.com](http://se.firesecurityproducts.com) online eller kontakta din försäljningsrepresentant.

Last updated on 26 June 2023 - 10:45